



Reliable

Rely on your equipment



Efficient

Get it done efficiently



Durable

Built for tough work

POWERFUL & PRECISE



- REDLINE Forward Plates
- REDLINE Reversible Plates
- REDLINE Walk Behind Roller
- REDLINE Drive Units & Pokers
- REDLINE Frequency Converters
- REDLINE Electronic Pokers
- REDLINE Cutters

Drive Your Success - Build it Red!

FORWARD PLATE



REDLINE RV50

Operating mass: 53 kg
Frequency: 100 Hz
Amplitude: 2.4 mm
Manufacturer/Power :
Honda GX 160/4.1 kW @ 3,600 rpm



REDLINE RV80

Operating mass: 78 kg
Frequency: 93 Hz
Amplitude: 1.44 mm
Manufacturer/Power :
Honda GX 160/4.1 kW @ 3,600 rpm



REDLINE RV100

Operating mass: 104 kg
Frequency: 93 Hz
Amplitude: 0.95 mm
Manufacturer/Power :
Honda GX 160/4.1 kW @ 3,600 rpm



REDLINE RV140D

Operating mass: 137 kg
Frequency: 93 Hz
Amplitude: 0.85 mm
Manufacturer/Power :
Greaves 1520/3.72 kW @ 3,600 rpm

REVERSE PLATE



REDLINE RR170D

Operating mass: 176 kg
Frequency: 91 Hz
Amplitude: 1.8 mm
Manufacturer/Power :
Greaves/3.72 kW @ 3450 rpm



REDLINE RR150

Operating mass: 151 kg
Frequency: 92 Hz
Amplitude: 1.65 mm
Manufacturer/Power :
Honda GX 160/4.1 kW @ 3,600 rpm



REDLINE RR180

Operating mass: 183 kg
Frequency: 81 Hz
Amplitude: 1.8 mm
Manufacturer/Power :
Honda GX 200/4.1 kW @ 3,450 rpm



REDLINE RR200D

Operating mass: 196 kg
Frequency: 81 Hz
Amplitude: 1.8 / 1.9 mm
Manufacturer/Power :
Hatz 1B20/Greaves 1520 / 3.3 kW
@3,450 rpm/3.72 kw @ 3,600 rpm

WALK BEHIND ROLLERS



REDLINE RW750D

Operating mass: 745 kg
Frequency: 60 Hz
Nominal Amplitude: 0.4 mm
Manufacturer/Power :
Kohler KD 441 / 6.6 kW @ 2,90 rpm

DRIVE UNITS & POKERS



REDLINE RD36

Operating mass: 28 kg
Fuel tank capacity: 3.1 l
Manufacturer/Power :
Honda GX160/3.6 kW @ 3,600 rpm



REDLINE RD37D

Operating mass: 59kg
Fuel tank capacity: 4.1 l
Manufacturer/Power :
Greaves 1520/3.67kW @ 3,600 rpm



REDLINE RD22e

Operating mass: 28 kg
Battery type: Electrical single phase
Manufacturer/Power :
Branded / 2.2 kW @ 2800 rpm



REDLINE RP30 / 45 / 60

Tube head diameter: 30/45/60 mm
Centrifugal force: 4.5/4.5/5.8 kN
Frequency: 12,000/12,000/11300 vpm

ELECTRONIC POKERS



REDLINE High Frequency Poker

Supply voltage: 42 volts
Frequency: 200 Hz



REDLINE Electronic Poker

Supply voltage: 230 volts
Frequency: 50/60 Hz
Exit voltage: 230 Volts 200 Hz



REDLINE Tube head diameter

Range: 38 / 50 / 60 / 70 mm
Hose length: 5m, 7m, 12m

FREQ CONVERTERS



REDLINE RF2

Mass: 18 kg
Number of outlets: 2
Input & Frequency: 230 V 1 50/60 Hz
Chassis model: Aluminium



REDLINE RF4

Mass: 54 kg
Number of outlets: 4
Input & Frequency: 400 V 3 50/60 Hz
Chassis model: Metallic

CUTTERS



REDLINE RC185

Operating mass: 135 kg
Max. cutting depth: 185 mm
Water tank capacity: 40 l
Manufacturer/Power :
Honda GX390/9.6 kW @ 3,600 rpm



REDLINE RC185D

Operating mass: 188 kg
Max. cutting depth: 185 mm
Water tank capacity: 40 l
Manufacturer/Power :
Greaves 1510/6.1 kW @ 3,600 rpm



DIAMOND CUTTER BLADE

Diameter: Standard 500 mm /
Optional 450 mm



RELIABLE

Rely on your equipment

- Do not compromise on quality, rely on the REDLINE products
- Easy operation and proven design ensure homogeneous results
- Convenient and professional support secures your equipment



EFFICIENT

Get it done efficiently

- Easy and simple machine built up provides the operator a clear and efficient working environment
- Reduces cost of ownership due to a lean machine design
- Maximize machine efficiency and security Dynapac Fleet management system



DURABLE

Built for tough work

- Powerful and durable equipment for demanding applications
- REDLINE uses high quality components for high wear resistance and long service intervals

**Dynapac Road Construction
Equipment (India) Pvt. Ltd.**

Plot No 1, Gat No. 163 - 168
Alandi Markala Road, Phulgaon,
Pune, Maharashtra - 412216
India
Email: customercare@dynapac.com
Customer Care No.: +91 7030626222